

The Monimax 5100 is a powerful, secure lobby model designed for both on- and off-premise locations. It can easily handle high-volume transactions.

Features

Powerful Performance

With a Windows XP platform and a Pentium processor, this ATM can handle high volume with minimal downtime. Plus, open-architecture software is now available on a 15" color TFT LCD.

Improved Security and Access

This ATM meets on-premise regulatory requirements. It has a UL291 Level 1 safe, PCI-certified encrypting PIN Pad, and offers ADA accessibility.

Small Footprint, Large Display

A 15" touch screen is both attractive and exceptionally secure. And with a small footprint, this lobby model can fit into tight spaces.

Visible Marketing Power

Vacuum Florescent Display (VFD) has exceptional clarity when seen from a distance. It attracts customers' attention—and is a great opportunity for promotional messages.

Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



The Monimax 5100 lets you grow with value-added functions and affordable upgrades.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 5100

System Control

- Intel® Pentium® processor
- Microsoft® Windows XP® platform
- Software: NDC+, DDC912, NHAP

Customer Display

- 15.1" TFT LCD
- Actual privacy filter

Communication

- Dial-up
- TCP/IP (SSL configurable)

Input Type

- Touch screen
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 2,000-note cassette
- Up to four cassettes
- 200-note reject bin

Printers

- 3.1" graphical thermal receipt printer

Security

- UL291 Level 1
- Standard electronic safe lock
- Optional dual safe lock (dial and key)
- Optional KABA Mas Cencon safe lock
- Optional security camera
- Optional electronic journal

Miscellaneous

- Optional heater
- Optional Vacuum Fluorescent Display (VFD)

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: 32°F–104°F
- Optional Tolerance: 14°F–104°F
- Humidity: 25%–86%

Dimension and Weight

- Height: 61.1" (1,552mm)
- Width: 18.1" (460 mm)
- Depth: 30.7" (780 mm)
- Weight: 694 lbs (315 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.