

Leveraging the experience and reliability of the world's leading convenience deployment brand, Nautilus Hyosung - the Monimax 5600 offers complete deployment flexibility and a broad range of non-traditional service offerings. Ideal for in-branch or off-premise deployments, the 5600 is a superior option when reliability, security, and high capacity are required.

Features

Superior, Flexible Design

The 5600 boasts one of the most efficient user interfaces available - 10% to 40% more compact than most competitors. The 5600 also offers a full range of advertising and marketing support along with a five high option for the dispenser. An industry standard 15.1" TFT may be complimented with an optional, unique vacuum fluorescent display (VFD) for unparalleled visibility.

Security

The 5600's UL-291 Level 1 rated safe has been proven in the field time and again, with independent third party attack tests revealing the ability of the Nautilus Hyosung enclosure to withstand attacks more severe and over a longer period of time than the UL rating requires. Additionally, market leading software and transactional security features are available as options, as are video surveillance cameras.

Dependability

Reliability derived from being the market leader in cash dispensing technology, and availability provided by high capacity modules, the 5600 is the ideal self-service platform for transaction intensive branch or off premise deployments.

Monimax 5600 is designed with speed in mind. Rapid transaction processing to cardholders, speedy service events enhanced by access by design, and quick deployments enabled by platform flexibility. All in one highly secure, reliable platform.



Hyosung - Always By Your Side. Nautilus Hyosung is more than reliable, proven self service technology. We are a company dedicated to the success of our partners.

MONIMAX 5600

System Control

- Intel® processor
- Microsoft® Windows® 7 platform
- NDC+, User Application

Communication

- TCP/IP

Customer Display

- 15" color TFT LCD
- Sunlight readable w/touch screen

Optional

- Privacy filter
- Touch screen

Input Type

- 4x2 function keys (option)
- PCI EPP (Encrypting PIN Pad)
- ADA compliant

Card Handling

- Dip-type card reader

Optional

- Anti-skimming

Cash Dispensing

- 3,000 notes cassette
(Up to 5 cassettes)
- Bundle retraction
- Automatic shutter

Printers

- 3.1" graphical thermal receipt printer
- Electronic journal
- 5,000 transactions

Security

- UL291 Level 1 safe
- Electronic safe lock

Optional

- KABA Mas Cencon safe lock
- Security camera

Miscellaneous

- Lead-through indicator

Optional

- VFD (Vacuum Fluorescent Display)

Power Supply

- AC 110 – 240V, 50–60Hz
- Backup battery

Operating Environment

- Temperature: 31°F – 104°F (0°C – 40°C)

Optional

- Humidity: 25%–85%

Dimension and Weight

- Height : 59.3" (1,505 mm)
- Width : 18.5" (470 mm)
- Depth : 29.9" (760 mm)
- Weight : 1093 lbs (495 kg) (Level 1 Safe)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

NH 5600
001_06/2011



Quality Data Systems
8655 Crown Crescent Court
Charlotte, NC 28227
sales@qualitydatasystems.com
1-800-258-1168