

Monimax™ 5600T

Value, Delivered

Features

- **Maximum Reliability** - Monimax 5600T is designed to provide 2nd to none reliability in the market with highest uptime and with minimum maintenance needs.
- **Environment Stewardship** - With quality comes also responsibility. Monimax series are equipped with energy saving features like low energy LCD and long lasting ATM parts with minimum implications to the environment.
- **Flexibility** - Monimax series are designed with open architecture platform allowing for easy future upgrades and module modifications. Modular design is one of ways in which we are trying to save our customers' cost and provide maximum convenience.
- **Ultimate Functionality** - Monimax 5600T offers ultimate functionality featuring bill payment, funds transfer, mobile top-up in a highly user friendly interface for maximum convenience and very easy transition.
- **Maximum Protection** - Complying to standards in various regions worldwide, Nautilus Hyosung offers advanced security measures while highly secured integrity of the Monimax 5600T prevents any attempted security breaches from occurring. Monimax 5600T is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Dependable Customer Service:

We understand the importance of speedy resolution to any issues arising in the operation. Our representatives offer real solutions with real results for maximum return on your investment.



System Control

- Intel® Pentium® IV processor
- Microsoft® Windows® XP platform
- NDC+, User Application

Communication

- TCP/ IP

Display

- 15" color TFT LCD
- Privacy filter
- Sunlight readable

Supervisor Operation

- 15" Color TFT LCD, touch screen

Input Type

- 8 function keys
- Touch screen
- PCI compliant EPP
T-DES, DES, RSA

Security

- UL 291 Level 1 safe

Optional

- Electronic lock
- KABA Mas cencen lock
- Security camera

Card reader

- Dip hybrid card reader
- Motorized hybrid card reader
- Contactless card reader
- EMV level 1,2 compliant
- Anti-skimming device

Cash dispenser

- 3,000 notes cassette
- Up to 4 cassettes
- Bundle present
- Bundle retraction
- Note by note rejection
- Automatic shutter

Printers

- Graphical thermal receipt printer
- Journal printer (Thermal, Dot)

Additional Features

- VFD(Vacuum fluorescent display)
- Lead-through indicator
- 1D/2D Barcode reader
- Heater
- Audio jack
- Speaker

Power Supply

- AC 110 ~ 240V, 50 ~ 60 Hz
- Backup battery
(Reserving last transaction & safe shutdown)

Environmental Conditions

- Temperature
0°C ~ 40°C (32°F ~ 104°F)
-31°C ~ 40°C (-24°F ~ 104°F) with heater
- Humidity
20% ~ 85%

Dimensions

- Height : 1,655mm (65.1")
- Width : 463mm (18.2")
- Depth : 1,111mm (43.7")
- Weight : 464kg (1,023 lbs)

All dimensions are without collar.

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

