

HITACHI Inspire the Next



The iH-210 Series Currency Discriminator Three Pocket Bank Note Counter

/O1: HIGH SPEED IMAGE PROCESSING TECHNOLOGY /O3: TWO TELLER / MULTI-USER MODE

/02: COMPACT SIZE AND LOW PROFILE /04: COLOR TOUCHSCREEN DISPLAY W/ ADJUSTABLE ANGLE



HITACHI Inspire the Next

The iH-210 Series combines the reliability and functionality of the iH-110 with an additional pocket.

The compact iH-210 uses minimum space to delivery maximum performance options.

FEATURES

COMPACT SIZE WITH TWO FULL FUNCTION POCKETS, PLUS REJECT POCKET:

- ► Similar size to 1.5 pocket machine
- Saving workspace and minimize the cash processing movement
- Selective pocket for fitness options: ATM, FIT, Reject

USER-FRIENDLY SYSTEM:

- ► 2-Teller mode/ Multi-user mode
- ► 5" Full LCD Color Touch Screen (Angle adjustable)

ADVANCED TECHNOLOGIES:

- ► Full color Dual CIS Sensor, Equipped with a range of counterfeit detection technologies
- ► Capture and Record OCR, MICR and Barcode
- Can be installed with up to 32 currencies
- Multi-currency mode (Up to 16 currencies can be counted at once)
- Reliable Fitness sorting/ Excellent tape detection performance

REMOTE MONITORING & MANAGEMENT SYSTEM:

► Related Application: Smart Integration Manager (SIM)

SPECIFICATIONS Up to 32 currencies including Mix & CNT **CURRENCY** (Mix & Multi up to 16 currencies) COUNTING Max. 1,300 Notes/min **OPERATING SPEED** VALUE/FITNESS COUNTING Max. 1,200 Notes/min SERIAL NUMBER RECOGNITION & PRINTING Max. 1,000 Notes/min **HOPPER** Max. 1,000 Notes **POCKET CAPACITY** STACKER X2 Max. 300 Notes (MINT CONDITION) **REJECT POCKET X1** Max. 200 Notes (MINT CONDITION) **DISPLAY** 480 x 272 TFT LCD (5 inch), Touch Screen 382 (W) x 417 (D) x 340 (H) mm **DIMENSION** Approx. 21 Kg **WEIGHT USER INTERFACE** LAN, USB(Serial) x 2, USB(host), RS232C x 3 **POWER SUPPLY** 100 - 240V ~ 50/60Hz Full Color Dual CIS Reflection (R, G, B, IR, UV) x 2, Transmission (IR) SENSOR INFORMATION Magnetic Sensor(Full Line) Thickness Detection Sensor (12 Channel) UV Reflection, Transmission (8 Channel) **OPTIONS** External LCD Display, Thermal Printer

