

# HYOSUNG

High Capacity Cash Dispensing ATM

# MX5300

## Hyosung is Revolutionizing the Self-Service Industry.

Being the ideal solution for off premise environments, the MX5300 offers an advanced design and includes a user-friendly interface displayed on a 15" screen. This full Windows model can handle whatever transaction set you can dream up. It's sophisticated look combined with it's high cash capacity make the MX5300 series a fantastic fit for both Retail and FI installs.

## Features

### HIGHEST AVAILABILITY

The **MX5300S** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

### HIGH CAPACITY

The **MX5300S** accommodates up to four 2,000 note cassettes for a maximum storage of 8,000 notes. The **MX5300S** is an ideal solution for off premise environments.

### INNOVATIVE DESIGN

The **MX5300S** features a user-friendly interface displayed on a vivid 15" screen.

### SECURITY OPTIONS

Hyosung ATMs defend against physical and logical attacks with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The **MX5300S** is also easily integrated with any monitoring solution to provide seamless data transfer for effective management.



## Specifications

### Dimensions

- Height: 55"
- Width: 18.1"
- Depth: 25.4"
- Weight: 617 lbs.

### Environmental Conditions

- Temperature: 32°F – 104°F  
(0°C ~ 40°C)
- Humidity 25% – 85%

### System Platform

- Microsoft Windows® 10

### Customer Interface

- 15" TFT LCD touch screen
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – DIP hybrid, EMV level 1, 2 compliant, anti-skimming
- Contactless – Integrated reader (via card, smartphone or smartwatch)

### Media Handling

- **Cash Dispenser**
  - Up to 4 cassettes
  - 2,000 notes per cassette

### Security

- Safe – UL291 business hours safe, level 1 safe (optional)
- Alarm – Seismic + heat
- Locking Device – Electronic safe lock, KABA mas cencon (optional)

### Printer

- 3.1" graphical thermal receipt printer

### Servicing

- Front Access
- State of health indicators for all modules

### Power Supply

- AC 100V ~ 127V±10%,  
200V ~ 240V±10% 50/60Hz

### Additional Features

- Communication – TCP/IP

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.