

HYOSUNG

MX5600

A robust, secure, and high-capacity solution.

The **MX5600** allows complete deployment flexibility and a broad range of non-traditional offerings. The **MX5600** is ideal for in-branch or off-premise deployments, and offers the best in class solution when high availability, security, and high capacity are required.

Features

Highest Availability

The **MX5600** is designed to provide exceptional reliability, unequalled in the market with minimum maintenance and maximum uptime.

Flexibility

Designed with an open architecture platform, the **MX5600** allows for easy future upgrades and module modifications. The modular design and compact footprint are designed to save our customers cost and provide maximum convenience. A full range of advertising and marketing support is available with the **MX5600**.

Capacity

The **MX5600** has high capacity, high cash dispense capability, and the ability to support large volume transactions.

Security Options

Hyosung ATMs defend against physical and logical with a combination of multi-level anti-skimming, locked down operating system, white-listing, and encryption. The **MX5600** is also easily integrated with any monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Specifications

Dimensions

- Height: 1508mm (59.3")
- Width: 467mm (18.2")
- Depth: 799mm (31.9")
- Weight: 443kg (978lbs)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- With Heater: -24°F – 104°F (-31°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10

Customer Interface

- 15" TFT LCD touch screen
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant
- Contactless – Integrated reader (via card, smartphone or smartwatch)

Media Handling

- **Cash Dispenser**
 - 3,000 notes per cassette
 - Configurable denominations
 - Up to 5 high capacity dispense cassettes
 - Bundle present/retract
 - Note by note rejection
 - Automatic shutter

Security

- Safe – UL291 level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic safe lock, KABA Mas Cencor
- Sensor – Safety door sensor
- Security – Terminal block for easy security connections
- Security camera

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Front Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

Additional Features

- Communication – TCP/IP

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.