

HYOSUNG

MX5600T

A robust, secure, and high-capacity through-the-wall solution.

The **MX5600T** allows complete deployment flexibility and a broad range of non-traditional offerings. Ideal for in-branch or off premise deployments, the **MX5600T** offers the best in class solution when high availability, security, and high capacity are required.

Features

Highest Availability

Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment, and reduced downtime. The **MX5600T** is designed to provide reliability that is unequaled in the market, with minimum maintenance and maximum uptime.

Flexibility

Designed with an open architecture platform, the **MX5600T** allows for easy future upgrades and module modifications. The **MX5600T** features a small footprint and compact design.

Capacity

The **MX5600T** has high capacity, cash dispense capability, and the ability to support large volume transactions.

Security Options

Hyosung ATMs defend against physical and logical attacks with a multi-level locked down operating system, white-listing, encryption, and anti-skimming.



Specifications

Dimensions

- Height: 1779mm (70.0")
- Width: 463.0mm (18.2")
- Depth: 1136.2mm (44.7")
- Weight: 500kg (1102.3 lbs)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10
- Hyosung Moniplus™ XFS

Customer Interface

- 15" LCD touch screen (function key optional)
- PIN Pad – PCI complaint
- ADA audio guidance – earphone jack
- Card Reader – DIP, EMV compliant, anti-skimming & anti-shimming (optional)
- Contactless – Integrated reader (via card, smartphone or smartwatch)

Media Handling

- **Cash Dispenser**
 - 3,000 notes per cassette*
 - Configurable denominations
 - Up to 4 cassettes
 - Bundle present/retract
 - Note by note rejection
 - Dispense up to 50 notes in a single transaction

Security

- Safe – UL291 level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic safe lock, KABA Mas Cencon (optional)
- Privacy Filter – 15" filter (optional)
- Security camera

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Rear Access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%, 200V ~ 240V±10% 50/60Hz

Additional Features

- Communication – TCP/IP
- Heater (optional)

*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.